

Ø300mm Horizontal Profile Projector



Product Features:

300mm diameter screen with digital protractor;

200X100mm precision movement work-stage;

Work-stage sway range between \pm 15°;

Halogen profile and fiber surface illumination adjustable;

Geometric multifunction data processing system upgrade to DRO DP100;

Built-in Mini-printer;

Available 10x,20x,50x,100x objective, over-chart and foot-switch edge detector etc.

Technical Specifications:

iPro-E11			
408x126mm			
200x100mm			
75mm (for focusing)			
0.0005mm			
±15°			
≤3+L/200(um)			
Diameter :Ø330mm,Effective Range ≥ Ø300(with "* " Reticle)			
Rotary Range: 0~360°; Resolution Rotary Indicator: 1' or 0.01°			
DP 100 Multifunctional Data Processing System			
Contour illumination:24v/150w (halogen Lamp)			
Surface illumination:21v/150w (Optical Fiber)			
Power Supply AC110V/60Hz; 220V/50Hz,650w			
1160x600x960mm			
1300x880x1250mm			
260/220kg			

Standard Delivery:

Digital Readout DP100	10x Objective	Screen Clamp Device	
Built-in Mini-printer	Power Cable	Operation Manual	

Optional Accessories:

Measuring Software	Working Cupboard	100X Objective	Edge Detector
20x Objective	50X Objective	Over-Chart	Rotary Vise
Holder Clamp	V-shape Clamp	Swivel Center Support	Foot-Switch